VOYAGER CELLDUO

VoyagerCell Duo is a rapidly deployable standards-based 4G LTE base station complete with a virtual machine server that together provide high-speed voice, video and data communications, along with mission-critical, localized applications and services, in a scalable, man-portable package.

VoyagerCell Duo's design guarantees service availability and independence from backhaul for fully self-contained operation while at the same time offering multiple eNodeB, Wi-Fi, vehicle and manpack options for increased flexibility.

KEY FEATURES

2 x 5W eNodeb with:

- 32/100 bearer variants
- · B14 for US Public Safety
- B28 for Euro Public Safety
- Built-in x86 compute server with Intel® 8-Core C3708 processor, 32 GB RAM running KlasOS Keel
- Voyager Ignition Key (VIK+) NVMe based storage with 512 GB capacity for rapid system configuration and reconfiguration by a minimally trained operator
- Single button operation with LCD screen for operator feedback
- Optional built-in 3G/LTE modem allows backhaul to MNO network or Wi-Fi modem for connection to 802.11 access point
- Optional Wi-Fi access point functionality to support 802.11 clients locally, supporting EAP-SIM authentication
- MIL-STD-1275D transient protection to allow for direct connection to vehicles



- Base system can be mounted and powered from two Voyager 8 backplane connectors while occupying a total of three Voyager 8 slots in total
- Handles and battery box or DC input can be attached for manpack operation



Portable





Rugged

Low Power

EMEA:

Klas

4th Floor, One Kilmainham Square, Inchicore Road, Kilmainham,

Dublin 8, Ireland
DO8 ETIW.

Tel: +353 1 6624270

US

Klas Government 450 Springpark Place, Suite 1200, Herndon, VA 20170

Tel: +1 571-375-2500

www.klasgroup.com



VOYAGER CELLDUO Specifications

CELLULAR SPECIFICATIONS

- Support for LTE Bands 1, 2, 3, 4, 5, 7, 13, 14,
 17, 20, 27, 28
- 3 MHz, 5 MHz 10 MHz and 20 MHz bandwidth options
- 3GPP Release 13

COMPUTE

- Intel® 8-Core C3708processor
- 32 GB RAM
- Running on KlasOS Keel operating system
- Additional GuestOS/applications as required

PHYSICAL SPECIFICATIONS

- Milled aluminum construction with fanless cooling
- Base configuration for use in Voyager 8
 - 7.4 x 8.7 x 5.6" (188 x 220.5 x 143mm)
 - 12.8 lb / 5.8 kg
- Manpack with Battery Box Configuration
 - 8.5" x 14.1" x 5.6" (216 x 359 x 143mm)
 - 18.8 lbs (8.55 kg) (Add 3.1 lb/1.4 kg for 2590 battery)
- Manpack with DC Input Configuration
 - 8.5 x 11.3 x 5.6" (216 x 286 x 143mm)
 - 16.5 lb (7.5 kg)

ELECTRICAL SPECIFICATIONS

- Input 10 36 VDC (14 36 VDC through battery box connector)
- 96 W (Maximum)
- 3.5 h battery operation with 2590 at 70%
 Tx (Class 9/ non-IATA compliant)
- 3 h battery operation with 2 cell battery unit at 70% Tx (IATA compliant)
- 6 h battery operation with 4 cell battery unit at 70% Tx (IATA compliant)

SAFETY

- EN 62368-1
- CE (Band 28 only)

INTERFACES


- 2 x Antenna connectors (50 Ω N-type)
- 2 x Antenna (SMA) Wi-Fi
- 2 x Antenna (SMA) Cellular
- 1xLCD screen
- 1x Voyager Ignition Key (VIK+) storage
- 1x Gigabit Ethernet compute port
- 1x Serial console port
- 1x GPS Antenna port (SMA)

COMPLIANCE

- MIL-STD-810H for:
- Vibration (514.8)
- Temperature High (501.7)
- Temperature Low (502.7)
- Humidity (507.6)
- Altitude (500.6)

EMC/EMF

- Radio Equipment Directive 2014/53/EU:
- EN 301 489-1
- EN 301 489-17
- EN 301 489-19
- EN 301 489-50
- EN 301 489-52
- EN 61000: -4-2, -4-3, -4-4, -4-5, -4-6,
- -4-8, -4-11
- EN 50663
- EN 50385



EMEA:

Klas

4th Floor, One Kilmainham Square, Inchicore Road, Kilmainham, Dublin 8, Ireland

DO8 ETIW.

Tel: +353 1 6624270

US

Klas Government 450 Springpark Place, Suite 1200, Herndon, VA 20170

Tel: +1 571-375-2500

www.klasgroup.com

