

# VOYAGER/8 QP

The Voyager 8 Quad Power (QP) is an eight slot chassis with four separate power elements for multi-enclave applications.

It is based on the award winning Voyager 8 carbon fibre case and chassis. The chassis power system can be divided into four quadrants so that four separately powered enclaves can exist within the Voyager 8 QP chassis and case.



## KEY FEATURES

- Voyager 8 form factor case and chassis
- Supports up to four enclaves
- AC or DC power with 250 W available per enclave
- Each enclave is powered via separate AC and DC power inlets to provide electrical isolation between enclaves
- Any power quadrant is field replaceable (FRU) and can be removed from the chassis without impacting the live functionality of other quadrants for ease of maintenance
- Battery back-up option available using the proven Voyager 1 or Voyager 1+ UPS if required



RUGGED



SECURE



VEHICLE POWERED

### EMEA

Klas,  
4th Floor, One Kilmainham Square,  
Inchicore Road, Kilmainham,  
Dublin 8, Ireland  
DO8 ETIW.  
Tel: +353 1 6624270

### US

Klas Government  
450 Springpark Place,  
Suite 1200,  
Herndon, VA 20170  
Tel: +1 571-375-2500

[www.klasgroup.com](http://www.klasgroup.com)

# KLAS

# VOYAGER/8 QP

## Specifications



### PHYSICAL SPECIFICATIONS

- 22.5" W x 14.2" D x 10.1" H (571 x 360 x 257 mm) with removable 19" rack mountable chassis
- 17.15 kg / 37.8 lbs

### CONSTRUCTION

- Aerospace-grade, multidirectional carbon fiber transit case
- Milled aluminum hardware
- Neoprene O-ring watertight seal
- Manual pressure equalization valve
- Aluminum sheet metal
- Milled aluminum latches
- Fan cooled (each power quadrant has an internal fan)
- 19" rack mountable

### HANDLES

- Retractable extension handle
- Grab handles on top and bottom of case

### OPERATING TEMPERATURE RANGE

- -40°C to 50°C

### STORAGE TEMPERATURE RANGE

- -40°C to 85°C

### ELECTRICAL INPUT SPECIFICATION

- 90 - 264 VAC via four separate C14 IEC inlets
- 18 to 40V (25 Amps max) via PT02E-12-8P MIL-STD-1275E
- M6 Earth stud

### ELECTRICAL OUTPUT SPECIFICATIONS

- Each power quadrant can deliver up to 250 W
- Each slot interface can deliver 12V at 120 W
- Each quadrant can deliver 52V at 60 W for PoE

### STANDARDS

- IEC 60529 IP67
- Built to MIL-STD-461
- Built to MIL-STD-810
- Built to MIL-STD-1275E
- CE
- FCC CFR 47 Part 15 Subpart B Class A
- RoHS Directive
- IEC 61000-4-2 & IEC 61000-4-5 Rugged



Voyager 8 QP Rear