

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Tankpatrone M0.35 Desert DE**

**TKZ: 303 905 089 / NSN: 6810-12-376-4737**

**Tankpatrone M2.5 Desert**

**TKZ: 303 905 070 / NSN: 6810-12-381-8737**

**Tankpatrone M28 Desert**

**TKZ: 303 905 079 / NSN: 6810-12-383-1620**

**Tankpatrone M0.35 Desert EN**

**TKZ: 303 905 091 / NSN: 6810-12-376-6203**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Fuel Cell

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

SFC Energy AG  
Eugen-Sänger-Ring 7  
85649 Brunnthal

Tel.: +49 (0)89 673-592-0  
Fax: +49 (0)89 673-592-369  
info@sfc.com

Distributor:  
Fuel Cell Systems Ltd.  
Station Yard  
RG17 0DY Hungerford, Berkshire  
GB  
Tel.: +44 1488507053

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

Page 2 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.09.2022 / 0008  
 Replacing version dated / version: 01.10.2021 / 0007  
 Valid from: 08.09.2022  
 PDF print date: 08.09.2022  
 Tankpatrone M0.35 Desert DE  
 TKZ: 303 905 089 / NSN: 6810-12-376-4737  
 Tankpatrone M2.5 Desert  
 TKZ: 303 905 070 / NSN: 6810-12-381-8737  
 Tankpatrone M28 Desert  
 TKZ: 303 905 079 / NSN: 6810-12-383-1620  
 Tankpatrone M0.35 Desert EN  
 TKZ: 303 905 091 / NSN: 6810-12-376-6203

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Flam. Liq.	2	H225-Highly flammable liquid and vapour.
Acute Tox.	4	H302-Harmful if swallowed.
Acute Tox.	3	H331-Toxic if inhaled.
Acute Tox.	3	H311-Toxic in contact with skin.
STOT SE	1	H370-Causes damage to organs.

### 2.2 Label elements

#### Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H225-Highly flammable liquid and vapour. H302-Harmful if swallowed. H331-Toxic if inhaled. H311-Toxic in contact with skin.  
 H370-Causes damage to organs.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.  
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260-Do not breathe vapours or spray. P264-Wash hands thoroughly after handling. P270-Do not eat, drink or smoke when using this product. P280-Wear protective gloves / protective clothing.  
 P308+P311-IF exposed or concerned: Call a POISON CENTER / doctor.  
 P405-Store locked up.  
 P501-Dispose of contents / container to an approved waste disposal facility.

Methanol

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).  
 Dangerous vapours heavier than air.  
 In case of spreading near the ground, flashback to distance sources of ignition is possible.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

Methanol	Substance for which an EU exposure limit value applies.
<b>Registration number (REACH)</b>	01-2119433307-44-XXXX
<b>Index</b>	603-001-00-X
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	200-659-6
<b>CAS</b>	67-56-1
<b>content %</b>	60-100
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370
<b>Specific Concentration Limits and ATE</b>	STOT SE 1, H370: $\geq 10$ % STOT SE 2, H371: $\geq 3$ % ATE (oral): 300 mg/kg

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

Medical supervision necessary due to possibility of delayed reaction.

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air. Call doctor immediately.

If the person is unconscious, place in a stable side position and consult a doctor.

Keep Data Sheet available.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap. Call a doctor immediately, keep datasheet at hand

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

#### Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

Induce vomiting.

Allow drinking approx. 100 ml approx. 40% ethanol in esculent.

Keep Data Sheet available.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Page 4 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.09.2022 / 0008

Replacing version dated / version: 01.10.2021 / 0007

Valid from: 08.09.2022

PDF print date: 08.09.2022

Tankpatrone M0.35 Desert DE

TKZ: 303 905 089 / NSN: 6810-12-376-4737

Tankpatrone M2.5 Desert

TKZ: 303 905 070 / NSN: 6810-12-381-8737

Tankpatrone M28 Desert

TKZ: 303 905 079 / NSN: 6810-12-383-1620

Tankpatrone M0.35 Desert EN

TKZ: 303 905 091 / NSN: 6810-12-376-6203

The following may occur:

After resorption:

Nausea

Vomiting

Headaches

Dizziness

Danger of blindness.

Acidosis

Drop in blood pressure

Cramps

Narcotic effect.

Coma

Liver and kidney damage

Disturbed heart rhythm

### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

CO<sub>2</sub>

Extinction powder

Water jet spray

Large fire:

Water jet spray / alcohol resistant foam

#### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Possible build up of explosive/highly flammable vapour/air mixture.

### **5.3 Advice for firefighters**

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

#### **6.1.1 For non-emergency personnel**

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid inhalation, and contact with eyes or skin.

Take measures against electrostatic charging, if appropriate.

If applicable, caution - risk of slipping.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.09.2022 / 0008

Replacing version dated / version: 01.10.2021 / 0007

Valid from: 08.09.2022

PDF print date: 08.09.2022

Tankpatrone M0.35 Desert DE

TKZ: 303 905 089 / NSN: 6810-12-376-4737

Tankpatrone M2.5 Desert

TKZ: 303 905 070 / NSN: 6810-12-381-8737

Tankpatrone M28 Desert

TKZ: 303 905 079 / NSN: 6810-12-383-1620

Tankpatrone M0.35 Desert EN

TKZ: 303 905 091 / NSN: 6810-12-376-6203

### **6.1.2 For emergency responders**

See section 8 for suitable protective equipment and material specifications.

### **6.2 Environmental precautions**

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

Danger of explosion.

### **6.3 Methods and material for containment and cleaning up**

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Use no flammable substances.

Flush residue using copious water.

Fill the absorbed material into lockable containers.

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### **7.1 Precautions for safe handling**

#### **7.1.1 General recommendations**

Ensure good ventilation.

If applicable, suction measures at the workstation or on the processing machine necessary.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Use explosion-proof equipment.

Earth devices.

Do not use on hot surfaces.

Also seal emptied tanks and tanks in the process after they have been used.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### **7.1.2 Notes on general hygiene measures at the workplace**

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### **7.2 Conditions for safe storage, including any incompatibilities**

Keep locked away.

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Solvent resistant floor

Do not store with flammable or self-igniting materials.

Protect against moisture and store closed.

Observe special storage conditions.

Store in a well ventilated place.

Protect from direct sunlight and warming.

Observe special storage conditions.

Store cool.

Page 6 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.09.2022 / 0008  
 Replacing version dated / version: 01.10.2021 / 0007  
 Valid from: 08.09.2022  
 PDF print date: 08.09.2022  
 Tankpatrone M0.35 Desert DE  
 TKZ: 303 905 089 / NSN: 6810-12-376-4737  
 Tankpatrone M2.5 Desert  
 TKZ: 303 905 070 / NSN: 6810-12-381-8737  
 Tankpatrone M28 Desert  
 TKZ: 303 905 079 / NSN: 6810-12-383-1620  
 Tankpatrone M0.35 Desert EN  
 TKZ: 303 905 091 / NSN: 6810-12-376-6203

Unsuitable material:  
 Various plastics  
 Magnesium  
 Zinc alloys

**7.3 Specific end use(s)**

No information available at present.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

Chemical Name	Methanol
WEL-TWA: 200 ppm (266 mg/m3) (WEL), 200 ppm (260 mg/m3) (EU)	WEL-STEL: 250 ppm (333 mg/m3 (WEL) ---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Alcohol 25/a Methanol (81 01 631)</li> <li>- Compur - KITA-119 SA (549 640)</li> <li>- Compur - KITA-119 U (549 657)</li> <li>- DFG Meth. Nr. 6 (D) (Loesungsmittelgemische 6), DFG (E) (Solvent mixtures 6) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 65-1 (2004)</li> <li>- NIOSH 2000 (METHANOL) - 1998</li> <li>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996</li> <li>- NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016</li> <li>- Draeger - Alcohol 100/a (CH 29 701)</li> </ul>
BMGV: ---	Other information: Sk (WEL, EU)

Methanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	15,4	mg/l	
	Environment - sediment, freshwater		PNEC	570,4	mg/kg	
	Environment - sediment, marine		PNEC	57,04	mg/kg	
	Environment - soil		PNEC	23,5	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	1540	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - inhalation	Long term, local effects	DNEL	26	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	26	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	4	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	26	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	4	mg/kg bw/day	

Consumer	Human - dermal	Long term, systemic effects	DNEL	4	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	26	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	4	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	20	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	130	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	130	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	20	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	130	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	130	mg/m3	

Ⓢ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Page 8 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.09.2022 / 0008  
 Replacing version dated / version: 01.10.2021 / 0007  
 Valid from: 08.09.2022  
 PDF print date: 08.09.2022  
 Tankpatrone M0.35 Desert DE  
 TKZ: 303 905 089 / NSN: 6810-12-376-4737  
 Tankpatrone M2.5 Desert  
 TKZ: 303 905 070 / NSN: 6810-12-381-8737  
 Tankpatrone M28 Desert  
 TKZ: 303 905 079 / NSN: 6810-12-383-1620  
 Tankpatrone M0.35 Desert EN  
 TKZ: 303 905 091 / NSN: 6810-12-376-6203

Chemical resistant protective gloves (EN ISO 374).  
 Recommended  
 With short-term contact:  
 Protective Viton® / fluoroelastomer gloves (EN ISO 374).  
 Permeation time (penetration time) in minutes:  
 > 120  
 With long-term contact:  
 Protective gloves in butyl rubber (EN ISO 374).  
 Permeation time (penetration time) in minutes:  
 > 480  
 References  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).  
 According to operation.  
 Protective working garment, antistatic (EN1149)  
 Natural fibre or heat-resistant synthetic fibre

Respiratory protection:  
 If OES or MEL is exceeded.  
 With short-term contact:  
 Gas mask filter AX (EN 14387), code colour brown.  
 With long-term contact:  
 Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colourless
Odour:	Alcoholic
Melting point/freezing point:	-98 °C (Methanol)
Boiling point or initial boiling point and boiling range:	>65
Flammability:	Flammable
Lower explosion limit:	5,5 Vol-% (Methanol)
Upper explosion limit:	44 Vol-% (Methanol)



Page 9 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.09.2022 / 0008  
 Replacing version dated / version: 01.10.2021 / 0007  
 Valid from: 08.09.2022  
 PDF print date: 08.09.2022  
 Tankpatrone M0.35 Desert DE  
 TKZ: 303 905 089 / NSN: 6810-12-376-4737  
 Tankpatrone M2.5 Desert  
 TKZ: 303 905 070 / NSN: 6810-12-381-8737  
 Tankpatrone M28 Desert  
 TKZ: 303 905 079 / NSN: 6810-12-383-1620  
 Tankpatrone M0.35 Desert EN  
 TKZ: 303 905 091 / NSN: 6810-12-376-6203

Flash point:	11 °C (Methanol)
Auto-ignition temperature:	455 °C (Methanol)
Decomposition temperature:	There is no information available on this parameter.
pH:	There is no information available on this parameter.
Kinematic viscosity:	There is no information available on this parameter.
Solubility:	Soluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,9 g/cm <sup>3</sup> (20°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

**9.2 Other information**

Explosives:	Possible build up of explosive/highly flammable vapour/air mixture. Product is not explosive.
Oxidising liquids:	No

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

The product has not been tested.

**10.2 Chemical stability**

Stable with proper storage and handling.

**10.3 Possibility of hazardous reactions**

No dangerous reactions are known.

**10.4 Conditions to avoid**

Heating, open flame, ignition sources  
 Electrostatic charge

**10.5 Incompatible materials**

Avoid contact with strong oxidizing agents.  
 Avoid contact with strong alkalis.  
 Avoid contact with strong acids.

**10.6 Hazardous decomposition products**

No decomposition when used as directed.

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Possibly more information on health effects, see Section 2.1 (classification).

**Tankpatrone M0.35 Desert DE**  
**TKZ: 303 905 089 / NSN: 6810-12-376-4737**  
**Tankpatrone M2.5 Desert**  
**TKZ: 303 905 070 / NSN: 6810-12-381-8737**  
**Tankpatrone M28 Desert**  
**TKZ: 303 905 079 / NSN: 6810-12-383-1620**  
**Tankpatrone M0.35 Desert EN**  
**TKZ: 303 905 091 / NSN: 6810-12-376-6203**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	500	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	500	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	5	mg/l/4h			calculated value, Vapours

Page 10 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.09.2022 / 0008  
 Replacing version dated / version: 01.10.2021 / 0007  
 Valid from: 08.09.2022  
 PDF print date: 08.09.2022  
 Tankpatrone M0.35 Desert DE  
 TKZ: 303 905 089 / NSN: 6810-12-376-4737  
 Tankpatrone M2.5 Desert  
 TKZ: 303 905 070 / NSN: 6810-12-381-8737  
 Tankpatrone M28 Desert  
 TKZ: 303 905 079 / NSN: 6810-12-383-1620  
 Tankpatrone M0.35 Desert EN  
 TKZ: 303 905 091 / NSN: 6810-12-376-6203

Acute toxicity, by inhalation:	ATE	0,83	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

<b>Methanol</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	ATE	300	mg/kg	Human being		Experiences on persons.
Acute toxicity, by dermal route:	LD50	17100	mg/kg	Rabbit		Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	85	mg/l/4h	Rat		Not relevant for classification., Vapours
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:				Mouse	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	1,3	mg/l	Mouse	OECD 416 (Two-generation Reproduction Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,13	mg/l	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	

Page 11 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.09.2022 / 0008  
 Replacing version dated / version: 01.10.2021 / 0007  
 Valid from: 08.09.2022  
 PDF print date: 08.09.2022  
 Tankpatrone M0.35 Desert DE  
 TKZ: 303 905 089 / NSN: 6810-12-376-4737  
 Tankpatrone M2.5 Desert  
 TKZ: 303 905 070 / NSN: 6810-12-381-8737  
 Tankpatrone M28 Desert  
 TKZ: 303 905 079 / NSN: 6810-12-383-1620  
 Tankpatrone M0.35 Desert EN  
 TKZ: 303 905 091 / NSN: 6810-12-376-6203

Symptoms:						abdominal pain, vomiting, headaches, gastrointestinal disturbances, drowsiness, visual disturbances, watering eyes, nausea, mental confusion, intoxication, dizziness
-----------	--	--	--	--	--	---

**11.2. Information on other hazards**

Tankpatrone M0.35 Desert DE TKZ: 303 905 089 / NSN: 6810-12-376-4737 Tankpatrone M2.5 Desert TKZ: 303 905 070 / NSN: 6810-12-381-8737 Tankpatrone M28 Desert TKZ: 303 905 079 / NSN: 6810-12-383-1620 Tankpatrone M0.35 Desert EN TKZ: 303 905 091 / NSN: 6810-12-376-6203						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

**SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Tankpatrone M0.35 Desert DE TKZ: 303 905 089 / NSN: 6810-12-376-4737 Tankpatrone M2.5 Desert TKZ: 303 905 070 / NSN: 6810-12-381-8737 Tankpatrone M28 Desert TKZ: 303 905 079 / NSN: 6810-12-383-1620 Tankpatrone M0.35 Desert EN TKZ: 303 905 091 / NSN: 6810-12-376-6203							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.

Page 12 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.09.2022 / 0008  
 Replacing version dated / version: 01.10.2021 / 0007  
 Valid from: 08.09.2022  
 PDF print date: 08.09.2022  
 Tankpatrone M0.35 Desert DE  
 TKZ: 303 905 089 / NSN: 6810-12-376-4737  
 Tankpatrone M2.5 Desert  
 TKZ: 303 905 070 / NSN: 6810-12-381-8737  
 Tankpatrone M28 Desert  
 TKZ: 303 905 079 / NSN: 6810-12-383-1620  
 Tankpatrone M0.35 Desert EN  
 TKZ: 303 905 091 / NSN: 6810-12-376-6203

12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

Methanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	15400	mg/l	Lepomis macrochirus		EPA-660/3-75-009
12.1. Toxicity to daphnia:	EC50	96h	18260	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	96h	22000	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	99	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		28400		Chlorella vulgaris		Not to be expected
Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	Log Pow		-0,77				
Other information:	DOC		<70	%			
Other information:	BOD		>60	%			

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 01 04 other organic solvents, washing liquids and mother liquors

13 07 03 other fuels (including mixtures)

Page 13 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.09.2022 / 0008  
 Replacing version dated / version: 01.10.2021 / 0007  
 Valid from: 08.09.2022  
 PDF print date: 08.09.2022  
 Tankpatrone M0.35 Desert DE  
 TKZ: 303 905 089 / NSN: 6810-12-376-4737  
 Tankpatrone M2.5 Desert  
 TKZ: 303 905 070 / NSN: 6810-12-381-8737  
 Tankpatrone M28 Desert  
 TKZ: 303 905 079 / NSN: 6810-12-383-1620  
 Tankpatrone M0.35 Desert EN  
 TKZ: 303 905 091 / NSN: 6810-12-376-6203

14 06 03 other solvents and solvent mixtures  
 Recommendation:  
 Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 E.g. suitable incineration plant.

**For contaminated packing material**

Pay attention to local and national official regulations.  
 Empty container completely.  
 Untampered packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.  
 Do not perforate, cut up or weld uncleaned container.  
 Residues may present a risk of explosion.  
 Recommended cleaner:  
 Water

**SECTION 14: Transport information**

**General statements**

14.1. UN number or ID number: 3473

**Transport by road/by rail (ADR/RID)**

14.2. UN proper shipping name:

UN 3473 FUEL CELL CARTRIDGES

14.3. Transport hazard class(es):

3

14.4. Packing group:

-

Classification code:

F3

LQ:

1 L

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

E

**Transport by sea (IMDG-code)**

14.2. UN proper shipping name:

FUEL CELL CARTRIDGES

14.3. Transport hazard class(es):

3

14.4. Packing group:

-

EmS:

F-E, S-D

Marine Pollutant:

n.a

14.5. Environmental hazards:

Not applicable

**Transport by air (IATA)**

14.2. UN proper shipping name:

Fuel cell cartridges

14.3. Transport hazard class(es):

3

14.4. Packing group:

-

14.5. Environmental hazards:

Not applicable

**14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

**14.7. Maritime transport in bulk according to IMO instruments**

Non-dangerous material according to Transport Regulations.



**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:

Page 14 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.09.2022 / 0008  
 Replacing version dated / version: 01.10.2021 / 0007  
 Valid from: 08.09.2022  
 PDF print date: 08.09.2022  
 Tankpatrone M0.35 Desert DE  
 TKZ: 303 905 089 / NSN: 6810-12-376-4737  
 Tankpatrone M2.5 Desert  
 TKZ: 303 905 070 / NSN: 6810-12-381-8737  
 Tankpatrone M28 Desert  
 TKZ: 303 905 079 / NSN: 6810-12-383-1620  
 Tankpatrone M0.35 Desert EN  
 TKZ: 303 905 091 / NSN: 6810-12-376-6203

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Regulation (EC) No 1907/2006, Annex XVII  
 Methanol  
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!  
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000
H2	7	50	200
H3		50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
22	Methanol		500	5000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 60 %

Observe incident regulations.

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 1-16  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Acute Tox. 4, H302	Classification according to calculation procedure.
Acute Tox. 3, H331	Classification according to calculation procedure.
Acute Tox. 3, H311	Classification according to calculation procedure.
STOT SE 1, H370	Classification according to calculation procedure.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.09.2022 / 0008

Replacing version dated / version: 01.10.2021 / 0007

Valid from: 08.09.2022

PDF print date: 08.09.2022

Tankpatrone M0.35 Desert DE

TKZ: 303 905 089 / NSN: 6810-12-376-4737

Tankpatrone M2.5 Desert

TKZ: 303 905 070 / NSN: 6810-12-381-8737

Tankpatrone M28 Desert

TKZ: 303 905 079 / NSN: 6810-12-383-1620

Tankpatrone M0.35 Desert EN

TKZ: 303 905 091 / NSN: 6810-12-376-6203

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - oral

Acute Tox. — Acute toxicity - inhalation

Acute Tox. — Acute toxicity - dermal

STOT SE — Specific target organ toxicity - single exposure

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

- EC European Community
- ECHA European Chemicals Agency
- EC<sub>x</sub>, EL<sub>x</sub> (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
- EEC European Economic Community
- EINECS European Inventory of Existing Commercial Chemical Substances
- ELINCS European List of Notified Chemical Substances
- EN European Norms
- EPA United States Environmental Protection Agency (United States of America)
- ErC<sub>x</sub>, ErμC<sub>x</sub>, ErL<sub>x</sub> (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
- etc. et cetera
- EU European Union
- EVAL Ethylene-vinyl alcohol copolymer
- Fax. Fax number
- gen. general
- GHS Globally Harmonized System of Classification and Labelling of Chemicals
- GWP Global warming potential
- Koc Adsorption coefficient of organic carbon in the soil
- Kow octanol-water partition coefficient
- IARC International Agency for Research on Cancer
- IATA International Air Transport Association
- IBC (Code) International Bulk Chemical (Code)
- IMDG-code International Maritime Code for Dangerous Goods
- incl. including, inclusive
- IUCLID International Uniform Chemical Information Database
- IUPAC International Union for Pure Applied Chemistry
- LC50 Lethal Concentration to 50 % of a test population
- LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
- Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
- Log Kow, Log Pow Logarithm of octanol-water partition coefficient
- LQ Limited Quantities
- MARPOL International Convention for the Prevention of Marine Pollution from Ships
- n.a. not applicable
- n.av. not available
- n.c. not checked
- n.d.a. no data available
- NIOSH National Institute for Occupational Safety and Health (USA)
- NLP No-longer-Polymer
- NOEC, NOEL No Observed Effect Concentration/Level
- OECD Organisation for Economic Co-operation and Development
- org. organic
- OSHA Occupational Safety and Health Administration (USA)
- PBT persistent, bioaccumulative and toxic
- PE Polyethylene
- PNEC Predicted No Effect Concentration
- ppm parts per million
- PVC Polyvinylchloride
- REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
- REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
- RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
- SVHC Substances of Very High Concern
- Tel. Telephone
- TOC Total organic carbon



Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.09.2022 / 0008

Replacing version dated / version: 01.10.2021 / 0007

Valid from: 08.09.2022

PDF print date: 08.09.2022

Tankpatrone M0.35 Desert DE

TKZ: 303 905 089 / NSN: 6810-12-376-4737

Tankpatrone M2.5 Desert

TKZ: 303 905 070 / NSN: 6810-12-381-8737

Tankpatrone M28 Desert

TKZ: 303 905 079 / NSN: 6810-12-383-1620

Tankpatrone M0.35 Desert EN

TKZ: 303 905 091 / NSN: 6810-12-376-6203

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.